

BIO SEA

by BIO UV
Group

IMO & USCG
TYPE APPROVED

BALLAST WATER TREATMENT STANDARD **B** RANGE

From 50 to 2000 m³/h


BIO-UV Group, created 20 years ago, is a leading European supplier of UV water and surface treatment solutions. The Group designs, manufactures and markets UV-C ballast water treatment systems, BIO-SEA®.



BIO-SEA B02-0300

Available in skid version and in containerized version

MODULAR



BENEFITS

- UV dose automatic regulation depending on water quality
- Tested in low UV water transmittance conditions with best results
- Safe: chemical free, zero by-product, zero active substances
- Not impacted by water temperature, neither by salinity
- Automatic operation, easy-to-use interface
- First Class marine components
- Easy to install, operate and maintain
- Cost efficient solution, low OPEX

CERTIFIED SALES AND SERVICE PARTNERS FOR TURNKEY SOLUTIONS

From a simple onboard visit, or a 3D laser scanning survey, to a high-level global turnkey package, BIO-SEA works with a **worldwide service network** of certified partners and suppliers for the whole range of BIO-SEA BWTS.



1st
STEP

MECHANICAL FILTRATION

- **20µm screen** to retain suspended solids and zooplankton
- **Sized to scale** depending on the flow rate to treat
- **Automatic backwash** with standard suction pump delivered with the system
- **No disruption of the filtration process** during the backwash cycle and no significant variation of the treated flow rate



2nd
STEP

UV DISINFECTION

- **Titanium reactor designed** with a single polychromatic, medium pressure, **high intensity UV lamp for optimum cost and treatment results**
- High-quality quartz sleeve protecting the UV lamp
- Optimized design by CFD (Computational Fluid Dynamic) taking into account water quality (UV transmittance) and fluid speeds, **allowing for easier cleaning and maintenance**
- Lamp driven by electronic ballast and UV sensor under monitoring allowing precise management of the UV lamp power to **optimize its intensity, reduce the power consumption** and prolong its life



MONITORING AND CONTROL

- **Easy to use thanks to its touch screen interface**
- **Standard fully automated operating modes** for ballasting, de-ballasting, cleaning and stripping
- Monitoring through sensors and PLC: UV and temperature sensors, flow meter, pressure transmitters, automatic valves
- **Touch screen interface** for easy friendly use, control and visualization
- **Recording of operations** and alarms covering 24 months, automatic generation of PDF reports
- Bus communication for remote control, integration to vessel automation system and control command



Option for an ultimate experience: remote control panels (7" or 15" auxiliary touch screen), AMS integration (RS 485 communication cabine), BIO-SEA Clean (automatic quartz sleeve cleaning system)

SPECIFICATIONS

Treatment Capacity	from 50 to 2000 m ³ /h
Power Supply	400 – 440V; 50-60 Hz; 3-phases
Power Consumption per UV reactor	12 kW - 22 kW
UV lamp lifetime	5000 hours
Environmental Operating Conditions	T°= 0°C - 55°C; H% ≤ 95
Global Head Loss	< 0,55 bars
Operating Pressure	1,5 - 10 bars

Other onboard BIO-UV Group environmental UV treatment solutions



Surface
treatment



Reuse



Drinking
Water



Grey
Waters



Legionella



Pools
& Spas

BIOSEA by **BIOUV**

850 avenue Louis Médard - 34400 LUNEL FRANCE

Tel : +33(0)4 99 133 911 / Fax : +33(0)4 99 133 919

www.ballast-water-treatment.com

bio-sea@bio-uv.com



This project is financed in part by the European Union funds for Regional Development in Occitanie, FR